

AD 2 AERODROMES

Note: The following sections in this chapter are intentionally left blank: AD-2.4, AD-2.5, AD-2.7, AD-2.10, AD-2.11, AD-2.14, AD-2.15, AD-2.16, AD-2.17, AD-2.18, AD-2.19, AD-2.20, AD-2.21, AD-2.22, AD-2.23, AD-2.24

RPLO AD 2.1 AERODROME LOCATION INDICATOR AND NAME

RPLO - CUYO PRINCIPAL AIRPORT (Class 2)

RPLO AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	ARP coordinates and site at AD	105140.4961N 1210405.0592E.
2	Direction and distance from (city)	8KM E.
3	Elevation/Reference temperature	36M AMSL.
4	Geoid undulation at AD ELEV PSN	Nil.
5	MAG VAR/Annual Change	1.9°W (2014) / 2.3' increasing.
6	AD Operator, address, telephone, telefax, telex, AFS	Civil Aviation Authority of the Philippines Cuyo Airport, Lucbuan Magsaysay, Cuyo 5318 Palawan
7	Types of traffic permitted (IFR/VFR)	VFR.
8	Remarks	Nil.

RPLO AD 2.3 OPERATIONAL HOURS

1	AD Operator	MON - FRI: 0000 - 0900.
2	Customs and immigration	Nil.
3	Health and sanitation	2200 - 1100.
4	AIS Briefing Office	Nil.
5	ATS Reporting Office (ARO)	Nil.
6	MET Briefing Office	Nil.
7	ATS	Nil.
8	Fuelling	Nil.
9	Handling	Nil.
10	Security	H24.
11	De-icing	Nil.
12	Remarks	Airport Operations: 2300 - 0800.

RPLO AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	Nil.
2	Rescue equipment	Wheel Type Fire Extinguisher.
3	Capability for removal of disabled aircraft	Nil.
4	Remarks	Nil.

RPLO AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: MACADAM. Strength: 7000KG.
2	Taxiway width, surface and strength	Width: Nil. Surface: Nil. Strength: 7000KG.
3	Altimeter checkpoint location and elevation	Nil.
4	VOR checkpoints	Nil.
5	INS checkpoints	Nil.
6	Remarks	Nil.

RPLO AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	SWY markers.
2	RWY and TWY markings and LGT	RWY: RWY markers. TWY: Nil.
3	Stop bars	Nil.
4	Remarks	Nil.

RPLO AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
04	040° GEO 040° MAG	800M X 30M	11818KG/0.5MPA MACADAM	Nil	Nil
22	220° GEO 220° MAG	800M X 30M	11818KG/0.5MPA MACADAM	Nil	Nil
Slope of RWY-SWY	SWY dimensions	CWY dimensions	Strip dimensions	OFZ	Remarks
7	8	9	10	11	12
0.5% uphill to the SW	60M X 30M 80M X 30M	220M 340M	Nil Nil	Nil Nil	Nil Nil

RPLO AD 2.13 DECLARED DISTANCES

RWY Designator	TORA	TODA	ASDA	LDA	Remarks
1	2	3	4	5	6
04	800M	1020M	860M	800M	C A O W W
22	800M	1140M	880M	800M	C A O W W